

FICHA TÉCNICA DE PRODUCTO

BROCA HORMIGON ARMADO CABEZA METAL DURO **REF. W77**



- Dimensiones: Según tabla.

- Cogida: SDS-plus



- Nº de placas: 1 integral
- Nº de cortes: 4



- Espiral de 4 canales (mayor extracción de polvo).
- Aplicación: hormigón armado; hormigón, manposteria, piedra natural, etc.
- Para realizar trabajos en percusión.
- Cuerpo: acero Aleado para herramientas.
- Placa de corte: Metal duro integral de alto rendimiento con punta autocentrante.
- Material empleado en su fabricación: Metal duro de grano fino Ceratizit CTF24-BC
- Tamaño grano Tungsteno: 0.8-1.3µm
- Densidad: 14.15 g/cm³
- Dureza: 1300 HV30 (89.7 HRA)

- Composición Metal grano fino (CTF24-BC)


RESPONSABLE DE CALIDAD:
RAÚL VERDUGO

CELESA, S.A.
Políg. Ind. Arriandi
C/ Tabernabarri, 5
48215 - Iurreta (Vizcaya)
Tel.: 946232532
Fax: 946201763

- Tungsteno (CW): 85%
- Aglutinante (Co): 12.5%
- Carburos mixtos (TaC; TiC; NbC): < 2%

D1 mm	L1 x L2 (mm)										
	115x50	165x100	215x150	250x200	265x200	315x250	365x300	450x400	465x400	600x550	1000x950
5,00											
5,50											
6,00											
6,50											
7,00											
8,00											
9,00											
10,00											
11,00											
12,00											
13,00											
14,00											
15,00											
16,00											
17,00											
18,00											
20,00											
22,00											
24,00											
25,00											
28,00											
30,00											

The drawing shows a side view of a mechanical component. It has a horizontal base with a vertical flange on the left. A horizontal arm extends from the flange. The length of the arm is labeled L1, and the length of the base is labeled L2. The drawing is a simple line sketch with dashed lines indicating the dimensions.



**RESPONSABLE DE CALIDAD:
RAÚL VERDUGO**

CELESA, S.A.
Políg. Ind. Arriandi
C/ Tabernabarri, 5
48215 - Iurreta (Vizcaya)
Tel.: 946232532
Fax: 946201763

A handwritten signature in blue ink, appearing to be 'R. Verdugo', written over a circular stamp or logo.